

## LATITUDE COMPETITION SERIES RIFLESCOPES

SPECIFICATIONS	SM13042FTR	SM13042PRS	SM13044BR	SM13044FTR
Reticle	F-Class	PRS	Benchrest	F-Class
Reticle type	etched	etched	etched	etched
Focal plane	second	first	second	second
Magnification	6.25-25	6.25-25	10-40	10-40
Objective lens diameter	56	56	60	60
Eye relief (in/mm)	4.7-4.2 / 120-107	4.7-4.2 / 120-107	4.1-3.8 / 103.8-96.5	4.1-3.8 / 103.8-96.5
Field of view (ft.@100yds)	16.1 - 4	16.1 - 4	10 - 2.5	10 - 2.5
Tube diameter (mm)	34	34	34	34
Parallax setting (yds)	20 - ∞	20 - ∞	20 - ∞	20 - ∞
Adjustment value (one click =)	1/4 MOA	.1 MRAD	1/8 MOA	1/8 MOA
Elevation adjustment range	110 MOA	31 MRAD	110 MOA	110 MOA
Windage adjustment range	70 MOA	20 MRAD	70 MOA	70 MOA
Battery type	CR2032	CR2032	CR2032	CR2032
Battery life (hours)	30-2,000	30-2,000	30-2,000	30-2,000

In the search for the perfect long-range precision optic, look no further than the Sightmark Latitude Competition Series Riflescopes. The Latitude is jam-packed with features found on scopes twice its price, including oversized adjustment turrets, a zero stop elevation dial and a locking, fast focus eyepiece. The Latitude's 34mm single-piece tube is ideal for long-distance shooting and is able to withstand up to .50 BMG caliber recoil. Its reticle can be illuminated red or green in low-light conditions. IP67 waterproof and fogproof, the Latitude offers protection from the elements with fully multi-coated optics. The Latitude comes with sunshade, CR2032 battery and manual.

